

Application type	Connection type	Max. operating temp.	Product description	Series	Page number
Wire to wire splicing	Solder	125°C	SolderSleeve wire splices	CWT-900X	9-6
		150°C	SolderSleeve wire splices	D-110, D-1744	9-6
	Crimp	125°C	DuraSeal crimp splices	D-406	9-16
	Coil and Solder	150°C	MiniSeal crimp splices	D-436 (M81824)	9-18
	Solder	125°C	SolderGrip closed end connector splices (stub)	SGRP, SGRS	9-12
Terminals and disconnects	Crimp	125°C	DuraSeal crimp terminals and disconnects	B-106	9-24
	Coil and Solder	125°C	SolderGrip terminals	SGRT	9-26
Wire termination to pin/post/tab	Solder	125°C	SolderSleeve wire terminators	CWT-15XX	9-32
		150°C	SolderSleeve wire terminators	D-129, D-141, D-71X	9-32
Shield termination	Solder	125°C	SolderSleeve shield terminators	CWT-X	9-36
		150°C	SolderSleeve shield terminators	S01, S02, M83519, SO63	9-36
		200°C	SolderSleeve shield terminators	SO96	9-36
Coax cable termination	Solder	125°C	SolderSleeve coaxial cable terminators	CWT-4XXX	9-42
		135°C	RF one-step BNC/TNC connector	RBD, RTD	9-47
		150°C	SolderSleeve coaxial cable terminators	B-02X/04X	9-42
			SolderSleeve PCB/coaxial cable terminators	D-607, B-046	9-45
Cable to cable splicing	Solder/Crimp	150°C	SolderShield cable splices	D-150, B-202	9-52
Shielded contacts	Solder	150°C	SolderTacts shielded contacts	D-602	9-56
MIL-STD-1553B data bus components	Solder	150°C	Data bus couplers, connectors, terminators, accessories	D-500, D-600, D(K)-621	9-60 through 9-68