

Product Specifications – Lacing Tapes

* A-A-52083B Finish D (MIL-T-43435B Type IV Finish D)

Product	Part Number	Width (+/- 10%)	Thickness (+/- .003")	Break Strength	Yards per Spool
TG-20	5401022001	.060"	.016"	50 lbs	500
TG-30	5401023001	.085"	.016"	75 lbs	500
TG-40	5401024001	.110"	.016"	100 lbs	250
TG-80	5401028001	.225"	.016"	200 lbs	250

Rockwell Space Division Spec MBO 135-035 Rev. G Type II (HT-30 Loc B only)

Product	Part Number	Width (+/- 0.015")	Thickness (0.025" max)	Break Strength	Yards per Spool
HT-20 Loc B	5421022097	.062"	.019"	45 lbs	500
HT-30 Loc B	5421023097	.090"	.019"	80 lbs	250
HT-40 Loc B	5421024097	.125"	.019"	100 lbs	250

Rockwell Space Division Spec MBO 135-035 Rev. G Type I

Product	Part Number	Width (+/- 0.015")	Thickness (0.025" max.)	Yards per Spool
HT-30 TVS	5411023001	.090"	.020"	250

* The General Services Administration has authorized the use of Commercial Item Description A-A-52083 as a replacement for Type IV of MIL-T-43435B for all federal agencies.