

Product Highlights

- Working temperature
-60°C to +250°C
- Good fluids resistance
- Easy to install
- Aesthetic solution
- Self-amalgamating
- Local Protection



Silicone Tapes 66N-67N-68N

The tapes 66N and 67N are silicone elastomer tapes, which self-amalgamates at ambient temperature. The maximum elongation ranges from 200% up to 500%.

Composed of a fiberglass base coated with self-amalgamating silicone elastomer, the tape 68N provides a high temperature mechanical protection.

After several hours at ambient temperature, the surface of these tapes sticks together when a light pressure is engaged.

These tapes are used for sealing, connecting and finishing the cut ends of sleeves exposed to high temperature. These products could also be used to protect locally harness parts and connection accessories.

BentleyHarris[®]
Protection Products

Performance Data

Silicone Tape 66N-67N-68N

Properties	Test	Results		
		66N	67N	68N
Working temperature		-60°C to +250°C		
Tensile strength		50 N	16.3 N	90 N
Elongation resistance		500 to 600%	200 to 300%	26%
Average dielectric strength	NFC 26.225	13KV/mm	16KV/mm	17KV/mm
Fluid Resistance <ul style="list-style-type: none"> • Jet Fuel JP5 • Hydraulic fluid Skydrol 500 B4 • Mineral oil NATO 0142 • Synthetic oil NATO 0156 • Cleaning fluids <ul style="list-style-type: none"> -MIL C 87836 -25% Propanol + 75% white spirit -Foran 141 B • Cooling fluid MIL- A -8243 	Immersion in the fluids for few seconds of the silicone tape amalgamate on its support (harness)	No deterioration to the amalgamate tape		

Product Specification

Description	Thickness	Width	Colour	Armed with glass tape	Packaging	NATO specification
Silicone Tape 66N	0.3 mm	19 mm	Red/Brown	No	15 Rolls	5870-14-467-8824
Silicone Tape 67N	0.5 mm	19 mm	Black	No	15 Rolls	5870-14-474-7041
Silicone Tape 68N	0.3 mm	19 mm	Red/Brown	Yes	15 Rolls	5970-14-464-7312

Recommendation time for perfect amalgamate

Temperature (°C)	250	200	150	127	120
Time in minute	15	20	35	80	120

Part Numbering System

Example:	Description	Size	Colour	Quantity
	66N	19 X 15 m	Standard	30

Availability

Bentley-Harris® Silicone Tape 66N, 67N and 68N are available in 15 meter rolls. Minimum order quantity is 15 rolls.

Packaging includes a polyester separating film to prevent layers from sticking. Standard colour is red/brown for 66N and 68N, black for 67N

The information and illustrations given herein are believed to be reliable. Federal-Mogul makes no warranties as to their accuracy or completeness and disclaims any liability in connection with their use. Federal-Mogul's only obligations are those in the standard term of sale for this product and Federal-Mogul will not be liable for any consequential or other damages arising out of the use or misuse of this product. Users should make their own evaluations to determine the suitability of the product for specific applications.

©1998 Federal-Mogul Systems Protection Group, manufacturer of Bentley-Harris protection products



Systems Protection Group

England/Rochdale
 Tel.: +44 (0) 1706 640 100
 Fax.: +44 (0) 1706 640 110
 France/Compiègne
 Tel.: +33 (0) 3 44 30 39 00
 Fax.: +33 (0) 3 44 30 39 49