

Product Construction: 2 Conductor Cable Shielded and Jacketed	Product Description EPD 22645	Issue A S'sedes
---	----------------------------------	--------------------

Designer <i>Colin Aldridge</i>	Date 03/07/84	Product Manager <i>Colin Field</i>	Date 03/07/84	Page 1 of 1
-----------------------------------	------------------	---------------------------------------	------------------	----------------

	Controlled Customer Copy SEL GERMANY
	Specifications Raychem WCD2002
	The copyright in this drawing is the property of Tyco Electronics UK Limited. The drawing is issued on condition it is not copied, reproduced or disclosed to a third party either in whole or in part without prior written consent of Tyco Electronics UK Limited.

Layer Type / Operation	Component Details <i>Part Numbers refer to issue in effect at date of issue of this EPD.</i>	Nominal O.D.mm
Components: Wire	2 of EPD22645A-01-9 Numbers as above	
Cabling: Layer 1	2 of EPD22645A-01 Fillers	11.3
Wrap:	Mylar	11.4
Shield: Optimised Braid	Tin Plated Copper AWG 34	12.1
Jacket: Extrusion 1	FDR 25 - Black	14.9 ±0.7
	<u>EPD 22645A-01</u>	<u>Nom. O.D. (mm)</u>
	Conductor - Rope Stranded: Tin Plated Copper AWG 8 (19x35x36AWG) 4.20 Jacket - Extruded: Thermorad - White 5.66	
Maximum Surface Transfer Impedance 50 milli ohms/metre	Notes De-Obsoleted 10/03/1994. Added to WORD 29/09/2000	Calculated nom. weight (Kg/Km) 370

If printed this document is an uncontrolled copy and reflects the issue status of the document on 26/10/2005 23:47

Lengths: Unless otherwise specified on your order this cable may be supplied in the following maximum number of continuous lengths:

Order Quantity (m) + One other length
 100

Tyco Electronics UK Ltd
 Faraday Road, Dorcan
 Swindon SN3 5HH
 Tel: (01793) 528171
 Telex: 449409

Registration Number:
 550926 London, England